



All types of fittings and necks

Ergonomic hand-holds

Recycleable PU jacket, CFC-free, UV stabilised, available in different colours

Safety bursting point



Character code datixPLUS, transponder, barcode

Coloured decor: in-mould coating or in-mould labelling

Smooth-walled stainless steel liner

Biologically safe

Repairs possible

Stable stacking rim

Soft Drink KEG

Technical Data

Stainless steel liner material	standard: mat. no. 1.4301, AISI 304 special: mat. no. 1.4571, AISI 316
Full coating:	PU (polyurethane), UV-stabilised
Partly coated:	10.4 l and 20.5 l
PU colour:	standard: black special colours: on request
Neck and fitting	standard SDK neck or neck with left-hand thread
Operating overpressure	7 bar
Test pressure	approx. 10 bar overpressure
Opening pressure of safety bursting point:	standard: 35 ± 5 bar overpressure 41 l SDK: 40 ± 5 bar overpressure
Coding (options)	Standard: datixPLUS/ alternative: transponder/barcode
Repairs:	partial only, new PU jacket possible

The **SOFT DRINK KEG** from SCHÄFER has many trend-setting benefits. Coca-Cola, Pepsi, Sinalco and many others are happy to rely on SCHÄFER expertise and have granted their approval for the production of all Soft Drink KEGs. This cool container proved a great success and was awarded the State Design Prize for its clarity and aesthetic appearance.

Polyurethane coated KEG with stainless steel liner, DIN compliant, in 10.4 l to 41 litre sizes or, partly coated, in 10.4 l or 20.5 litre sizes. Ideal for all soft drinks.



SOFT DRINK KEG DIN 6647-2

Content	10.4 l 2.75 US gal	15.5 l 4.10 US gal	20.5 l 5.42 US gal	41 l 10.83 US gal
Filling volume	10 l	15 l	20 l	40 l
Height	326 mm	443 mm	560 mm	510 mm
External Ø	239 mm	239 mm	239 mm	381 mm
Weight ¹	approx. 3.8 kg	approx. 4.6 kg	approx. 5.5 kg	approx. 10.4 kg

US gal = 3.785 l ¹ weight with L type fitting